

FNW™

Product Portfolio

Ask about our expanding selection of FNW products.



Your Piping Products Source

Since it was established in 1979, FNW has been dedicated to providing quality products for industrial and commercial applications. With a basic philosophy to provide a product suited to the needs of the end user, FNW has built a product offering with an innovative approach to the market and has continued to grow its product range to meet those needs. This brochure is an overview of our product range, however we are not limited to it. If you do not see the type or size of item needed for your application, please contact us.

Main Office: 4120 NE Columbia Blvd, Portland, OR 97211
Phone (503) 287-8383, Fax (503) 281-9677

See our web site for the latest additions to our product offering. We continue to add products that may not be reflected in this brochure. Updates and additional information are also available at: www.FNW.com.



Figure 60R
**KNIFE GATE VALVE FOR
ABRASIVE APPLICATIONS**

- CAST CS BODY/YOKE/FOLLOWER
- RESILIENT SEAT
- POP-OUT SLEEVE-LINED
- BI-DIRECTIONAL SHUTOFF
- UP TO 100 PSI CWP
- SIZES 3" - 30"



Figure 61B
**LINED KNIFE GATE VALVE,
METAL SEATED**

- CAST DI BODY/SS LINED
- METAL SEAT
- SS WETTED PARTS
- UNI-DIRECTIONAL SHUTOFF
- ECONOMY VALVE FOR MANY APPLICATIONS
- SIZES 3" - 24"



Figure 62B
**LINED KNIFE GATE VALVE,
RESILIENT SEATED**

- CAST DI BODY/SS LINED
- POSITIVE SHUTOFF RESILIENT SEAT
- SS WETTED PARTS
- UNI-DIRECTIONAL SHUTOFF
- ECONOMY VALVE FOR MANY APPLICATIONS
- SIZES 3" - 24"



Figure 65B
**CAST SS KNIFE GATE VALVE,
METAL SEATED**

- CAST SS BODY/YOKE/FOLLOWER
- METAL SEAT
- UNI-DIRECTIONAL SHUTOFF
- DESIGNED FOR HEAVY MEDIA
- REDUCED HW TORQUE 6" AND UP
- SIZES 2" - 24"



Figure 67B
**CAST SS KNIFE GATE VALVE,
METAL SEATED**

- CAST SS BODY AND YOKE
- METAL SEAT
- UNI-DIRECTIONAL SHUTOFF
- DESIGNED FOR HEAVY MEDIA
- NON-CLOGGING STEP SEAT DESIGN
- SIZES 3" - 30"



Figure 68B
**CAST SS KNIFE GATE VALVE,
RESILIENT SEAT**

- CAST SS BODY AND YOKE
- POSITIVE SHUTOFF RESILIENT SEAT EVEN AT LOW MEDIA PRESSURES
- BI-DIRECTIONAL SHUTOFF
- REDUCED HW TORQUE 14" AND UP
- SIZES 3" - 30"



Figure 2000B
**HIGH PERFORMANCE
KNIFE GATE VALVE**

- CAST SS BODY/YOKE/FOLLOWER
- FLEX TEFLON RESILIENT SEATS
- BI-DIRECTIONAL SHUTOFF
- REDUCED HW TORQUE 6" AND UP
- OPTIONAL CAST SS V-PORT INSERT
- SIZES 2" - 24"



Figure 2000BTIV
**TRANSMITTER ISOLATION
VALVE**

- CAST SS BODY/YOKE/FOLLOWER
- FLEX TEFLON RESILIENT SEATS
- BI-DIRECTIONAL SHUTOFF
- RATCHET OPERATOR
- ANSI J7 TANK SIDE FLANGE
- SIZE 3"



- F-SERIES
FABRICATED SLIDE AND
KNIFE GATE VALVES**
FABRICATION CAPABILITIES FOR:
- CUSTOM MATERIALS
 - CUSTOM PRESSURE RATINGS
 - CUSTOM SIZES
 - F150 SLIDE GATE OPTION
 - F65 AND F68 KNIFE GATE OPTION
 - CUSTOM CONFIGURATIONS



- Figure 160
HDPE SLIDE GATE VALVE
- DESIGNED FOR HIGH ABRASION
 - FULL FLOW O-PORT DESIGN
 - BI-DIRECTIONAL SHUTOFF
 - OPTIONAL VICTAULIC® OR PLAIN
 - FUSION ENDS AVAILABLE
 - SIZES 3" - 12"



- Figure 400 / 401
**2 PC FULL PORT 600 WOG
BRASS BALL VALVE**
- NPT (400), SWEAT (401)
 - RATED 150 WSP
 - NSF-61 RATED
 - MEETS MSS SP-110 STANDARDS
 - OPTIONAL LOCKING DEVICE, T-HANDLE, AND STEM EXTENSION
 - SIZES 1/2" - 2"



- Figure 410 / 411
**2 PC FULL PORT 600 WOG
BRASS BALL VALVE**
- NPT (410), SWEAT (411)
 - RATED 150 WSP
 - NSF-61 RATED
 - FIG. 410 - FM, UL, CSA RATED
 - SIZES 1/4" - 4" NPT, 1/2" - 3" SWEAT



- Figure 420 / 421
**2 PC FULL PORT 600 WOG
BRASS BALL VALVE**
- NPT (420), SWEAT (421), RATED 150 WSP
 - NSF-61 RATED
 - FIG. 420 - FM, UL, CSA & GAS RATED
 - FIG. 420 - OPTIONAL SS TRIM
 - OPTIONAL LOCKING DEVICE, T-HANDLE, AND STEM EXTENSION
 - SIZES 1/4" - 4" NPT, 1/2" - 4" SWEAT



- Figure 426 / 427 / 428
**2 PC FULL PORT 600 WOG
3/4" HOSE CONNECTION
BRASS BV**
- 3/4" HOSE CONNECTION
 - FULL PORT
 - WITH FNPT END (426), SWEAT END (427), MNPT (428)
 - INCLUDES CAP, CAP GASKET, & CHAIN
 - FORGED BRASS BODY & END CAP
 - SIZES 1/2" & 3/4"



- Figure 430
**200 PSI PRESS CONNECTION
BRASS BALL VALVE FOR
WATER SERVICE**
- FULL PORT DESIGN
 - NSF-61, FM & UL RATED
 - FORGED BODY & END CAP
 - BLOWOUT-PROOF STEM
 - ADJUSTABLE PACKING
 - SIZES 1/2" - 2" & 2-1/2" - 4" XL



- Figure 435
**125 PSI PRESS CONNECTION
BRASS BALL VALVE FOR GAS
SERVICE**
- FULL PORT DESIGN
 - CSA RATED
 - FORGED BODY & END CAP
 - BLOWOUT-PROOF STEM
 - ADJUSTABLE PACKING
 - SIZES 1/2" - 2"



- Figure 470 / 475
**2 PC FULL PORT 400 WOG
PUMP ISOLATION BALL VALVE**
- INTEGRAL PUMP FLANGE CONNECTION
 - FULL PORT DESIGN
 - FNPT END (470), SWEAT END (475)
 - INCLUDES T-HANDLE, GASKET & BOLTS
 - EASES PUMP INSTALL & REMOVAL
 - ADJUSTABLE PACKING
 - SIZES 3/4" - 1-1/2"



- Figure 100
**1 PC STANDARD PORT 800
WOG STAINLESS STEEL BALL
VALVE**
- INVESTMENT CAST BODY & END CAP
 - SS LOCKING HANDLE
 - RTFE SEATS
 - BLOWOUT-PROOF STEM
 - SIZES 1/4" - 2"



- Figure 200
**2 PC FULL PORT 1000 WOG
STAINLESS STEEL BALL
VALVE**
- INVESTMENT CAST BODY & END CAP
 - SS LOCKING HANDLE
 - RTFE SEATS
 - BLOWOUT-PROOF STEM
 - SIZES 1/4" - 2"



- Figure 220 / 220C - SSxSS
Figure 221 / 221C - CSxSS
**2 PC FULL PORT 2000 WOG
BALL VALVE**
- INVESTMENT CAST BODY & END CAP
 - SS LOCKING HANDLE
 - RTFE SEAT (220C/221C CARBON FILLED)
 - BLOWOUT-PROOF STEM
 - DRILLED & TAPPED MOUNTING PAD
 - SIZES 1/4" - 3"



Figure 260
2 PC ECONOMY 1000 WOG STAINLESS STEEL BALL VALVE

- FULL PORT
- INVESTMENT CAST BODY & END CAP
- RTFE SEATS
- SS LOCKING HANDLE
- BLOWOUT-PROOF STEM
- SIZES 1/4" - 2"



Figure 310 - SSxSS
Figure 311 - CSxSS
3 PC FULL PORT 1000 WOG BALL VALVE

- INVESTMENT CAST BODY & END CAPS
- NPT END (OPTIONAL SOCKET WELD)
- SS LOCKING HANDLE
- RTFE SEAT
- BLOWOUT-PROOF STEM
- SIZES 1/4" - 4"



Figure 320 / 320C - SSxSS
Figure 321 / 321C - CSxSS
3 PC FULL PORT 2000 WOG BALL VALVE

- INVESTMENT CAST BODY & END CAPS
- NPT END (OPTIONAL SOCKET WELD)
- SS LOCKING HANDLE
- RTFE SEATS (150 WSP RATED w/ OPTIONAL CARBON FILLED SEATS)
- SIZES 1/4" - 2"



Figure 360
3 PC ECONOMY 1000 WOG STAINLESS STEEL BALL VALVE

- FULL PORT
- INVESTMENT CAST BODY & END CAPS
- NPT END (OPTIONAL SOCKET WELD)
- SS LOCKING HANDLE
- RTFE SEATS
- SIZES 1/4" - 4"



Figure 330CE
SANITARY 3 PC FULL PORT 1000 WOG SS BALL VALVE

- CLAMP ENDS (OPTIONAL TUBE ENDS)
- CAVITY FILLED SEATS
- SILICON FREE CONSTRUCTION
- SS LOCKING HANDLE
- PTFE SEATS
- SIZES 1/2" - 4"



Figure 440
2 PC FULL PORT 600 WOG ISO MOUNT BRASS BALL VALVE

- ISO 5211 MOUNTING PAD
- RATED 150 WSP
- O-RING BACKED SEATS
- DOUBLE O-RING VITON® PACKING
- FOR DIRECT MOUNT ACTUATION
- SIZES 1/4" - 4"



Figure 220M
2 PC FULL PORT 2000 WOG ISO MOUNT SS BALL VALVE

- ISO 5211 MOUNTING PAD
- LIVE LOADED PACKING
- INVESTMENT CAST BODY & END CAP
- RTFE SEATS
- FOR DIRECT MOUNT ACTUATION
- SIZES 1/4" - 3"



Figure 310M
3 PC FULL PORT 1000 WOG ISO MOUNT SS BALL VALVE

- ISO 5211 MOUNTING PAD
- LIVE LOADED PACKING
- INVESTMENT CAST BODY & END CAPS
- NPT ENDS (OPTIONAL SOCKET WELD)
- RTFE SEATS
- FOR DIRECT MOUNT ACTUATION
- SIZES 1/4" - 4"



Figure 500 - SSxSS
Figure 501 - CSxSS
1 PC STANDARD PORT 150# FLANGED BALL VALVE

- INVESTMENT CAST BODY
- ANTI-STATIC DESIGN
- RTFE SEATS
- ISO MOUNTING PAD
- API 6D APPROVED
- SIZES 2" - 6"



Figure 600 - SSxSS
Figure 601 - CSxSS
2 PC FULL PORT 150# FLANGED BALL VALVE

- INVESTMENT CAST BODY
- ANTI-STATIC DESIGN
- RTFE SEATS
- ISO MOUNTING PAD
- API 6D APPROVED
- SIZES 1/2" - 10"



Figure 660
2 PC FULL PORT 150# FLANGED ECONOMY BALL VALVE

- INVESTMENT CAST BODY
- ANTI-STATIC DESIGN
- RTFE SEATS
- ISO MOUNTING PAD
- SIZES 2" - 6"



Figure 413
3-WAY DIVERTER 400 WOG BRASS BALL VALVE

- NPT END CONNECTIONS
- L-PORT CONFIGURATION
- RATED 150 WSP
- RTFE SEATS
- BLOWOUT-PROOF STEM
- ACTUATOR MOUNTING PAD
- SIZES 1/4" - 2"



- Figure 455 / 465
3-WAY 400 WOG ISO MOUNT BRASS BALL VALVE
- T-PORT (455) & L-PORT (465)
 - ISO 5211 MOUNTING PAD (WITH HANDLE)
 - RATED 100 WSP
 - O-RING BACKED SEATS
 - DOUBLE O-RING VITON® PACKING
 - FOR DIRECT MOUNT ACTUATION
 - SIZES 1/4" - 2"



- Figure 233
3-WAY DIVERTER 1000 WOG STAINLESS STEEL BALL VALVE
- STANDARD PORT
 - RTFE SEATS
 - SS LOCKING HANDLE
 - BLOWOUT-PROOF STEM
 - ACTUATOR MOUNTING PAD
 - SIZES 1/2" - 2"



- Figure 633 / 634
3-WAY 150# FLANGED STAINLESS STEEL BALL VALVE
- L-PORT (633) & T-PORT (634)
 - FULL PORT SPLIT BODY
 - RTFE SEATS
 - TOP ENTRY, TRUNNION MOUNTED BALL
 - ACTUATOR MOUNTING PAD
 - SIZES 2" - 10"



- Figure 731 / 732
RESILIENT SEATED BUTTERFLY VALVES
- WAFER (731) & LUGGED (732)
 - RATINGS UP TO 255 PSI
 - 316SS DISC & STEM STANDARD
 - ISO 5211 MOUNTING PAD
 - 2 PC PINLESS STEM
 - CARTRIDGE STYLE SEAT
 - SIZES 2" - 24"



- Figure HP
HIGH PERFORMANCE RESILIENT SEATED BUTTERFLY VALVES
- BI-DIRECTIONAL BUBBLE-TIGHT SEAT
 - DOUBLE OFF-SET DESIGN
 - WAFER OR LUGGED CONNECTIONS
 - SS OR CS BODY
 - ISO TOPWORKS
 - GEAR STANDARD (8" - 24")
 - SIZES 3" - 24"



- Figure 340 / 340F / 350
THERMOPLASTIC FULL PORT DOUBLE UNION BALL VALVE
- PVC (340/340F) & CPVC (350)
 - BOTH NPT & SW ENDS (UP TO 2")
 - ABOVE 2" IN SW (NPT ON REQUEST)
 - FULL PORT BI-DIRECTIONAL DESIGN
 - PTFE SEAT, EPDM OR VITON® SEALS
 - SIZES 1/2" - 4"



- Figure 721
THERMOPLASTIC WAFER BUTTERFLY VALVE
- 150 PSI TO 10", 12" TO 100 PSI
 - COMPACT DESIGN
 - BUBBLE-TIGHT SHUTOFF
 - EPDM OR VITON® SEAT/SEALS
 - CAN BE EASILY ACTUATED
 - SIZES 2" - 12"



- Figure 345 - PVC
 Figure 355 - CPVC
THERMOPLASTIC DOUBLE UNION BALL CHECK VALVE
- BOTH NPT & SW ENDS
 - 150 PSI MAX. WORKING PRESSURE
 - 5 PSI MINIMUM SHUTOFF
 - FOR VERTICAL INSTALLATION
 - EASY MAINTENANCE
 - SIZES 1/2" - 2"




- Figure 1201
STANDARD CAPACITY WATER PRESSURE REDUCING VALVE
- 300 PSI MAX WORKING PRESSURE
 - 25 - 75 PSI OUTPUT RANGE
 - FNPT UNION INLET
 - BUILT IN BYPASS
 - INTEGRAL STAINLESS STEEL STRAINER
 - IN-LINE SERVICEABLE
 - SIZES 1/2" - 1"



- Figure SC / SWA
WATER HAMMER ARRESTORS
- MALE NPT (SC) & COPPER SWEAT (SWA)
 - 600 PSI MAX
 - 60 - 400 PSI WORKING PRESSURE
 - LOW LEAD BRASS
 - FOR POTABLE WATER SERVICE
 - ASSE 1010-2004 LISTED
 - IAPMO LISTED (UPC)



- Piping Products
IPS DUCTILE IRON BACK-UP FLANGES
- 150# DRILLING
 - IPS SIZES
 - RED PRIMER OR HOT DIPPED GALVANIZED
 - LIGHT WEIGHT PATTERN
 - STUB END (SE) SIZES 1/2" - 36"
 - ANGLE FACE RING (AFR) SIZES 1" - 36"



- Piping Products
FLANGE GASKETS
- 150# & 300# NON-ASBESTOS RING
 - 150# NON-ASBESTOS FULL FACE
 - 150# RED RUBBER RING
 - 150# RED RUBBER FULL FACE
 - 1/16" & 1/8" THICK



Figure 1211 / 1212
NON-RISING STEM 125# BRONZE GATE VALVE

- 200 WOG
- 125 PSI SATURATED STEAM RATED
- SOLID WEDGE DISC
- FNPT ENDS (1211) & SWEAT ENDS (1212)
- BACK SEAT DESIGN
- CONFORMS TO MSS SP-80
- 1211 SIZES 1/4" - 3"
- 1212 SIZES 1/2" - 3"



Figure 1221 / 1222
RISING STEM 125# BRONZE GATE VALVE

- 200 WOG
- 125 PSI SATURATED STEAM RATED
- SOLID WEDGE DISC
- FNPT ENDS (1221) & SWEAT ENDS (1222)
- BACK SEAT DESIGN
- CONFORMS TO MSS SP-80
- SIZES 1/2" - 3"



Figure 1231 / 1232
125# BRONZE GLOBE VALVE

- 200 WOG
- 125 PSI SATURATED STEAM RATED
- RESILIENT SEAT DISC
- FNPT ENDS (1231) & SWEAT ENDS (1232)
- CONFORMS TO MSS SP-80
- 1231 SIZES 1/4" - 3"
- 1232 SIZES 1/2" - 2"



Figure 1241 / 1242
150# Y-PATTERN BRONZE SWING CHECK VALVE

- 300 WOG
- 150 PSI SATURATED STEAM RATED
- RESILIENT SEAT DISC
- FNPT ENDS (1241) & SWEAT ENDS (1242)
- CONFORMS TO MSS SP-80
- SIZES 1/2" - 3"



Figure 509 / 510
BRONZE Y-STRAINER

- FNPT ENDS (509) & SWEAT ENDS (510)
- 509 IS 250 WOG, 150 PSI STEAM
- 510 IS 400 WOG, 250 PSI STEAM
- CAST BRONZE BODY
- 20 MESH STAINLESS STEEL SCREEN
- BLOW-OFF PLUG INCLUDED
- 509 SIZES 3/8" - 2"
- 510 SIZES 1/2" - 2"



Figure 431
200 PSI PRESS CONNECTION BRASS IN-LINE CHECK VALVE FOR WATER

- HIGH CAPACITY DESIGN
- LOW 1/2 PSI CRACKING PRESSURE
- SOFT SEAT FOR TIGHT SHUTOFF
- NSF-61 APPROVED
- FORGED BODY & END CAP
- SIZES 1/2" - 2"



Figure 15B-200
THREADED SS 200 WOG NON-RISING STEM GATE VALVE

- STAINLESS STEEL TRIM
- ADJUSTABLE PACKING
- SIZES 1/2" - 2"



Figure 17B-200
THREADED SS 200 WOG GLOBE VALVE

- STAINLESS STEEL TRIM
- ADJUSTABLE PACKING
- SIZES 1/2" - 2"



Figure 16B-200
THREADED SS 200 WOG SWING CHECK VALVE

- STAINLESS STEEL TRIM
- PTFE SEALS
- SIZES 1/4" - 2"



Figure 14B-YSS
THREADED SS 800 PSI CWP Y-STRAINER

- SS 20 MESH SCREEN
- VITON® O-RING SEAL
- SIZES 1/2" - 2"



Figure 651 / 661 / 671
125# IRON BODY, BRONZE MOUNTED VALVE

- IBBM GATE (651), GLOBE (661), & CHECK (671) VALVES
- 125 PSI SWP (SATURATED TO 353°F)
- DESIGN AND TESTED TO:
 - GATES: MSS SP-70
 - GLOBES: MSS SP-85
 - CHECKS: MSS SP-71



Figure 558 / 559
CAST IRON Y-STRAINER

- 125# FLANGED ENDS (558) & FNPT ENDS (510)
- 558 IS 200 WOG, 125 PSI STEAM
- 559 IS 400 WOG, 250 PSI STEAM
- STAINLESS STEEL SCREEN
- BLOW-OFF PLUG INCLUDED
- 558 SIZES 2" - 12"
- 559 SIZES 1/4" - 3"



Figure 451 / 452 - SS
Figure 551 / 552 - CS
FLANGED OS&Y WEDGE GATE VALVE

- 150# FLANGES (451/551)
- 300# FLANGES (452/552)
- API 600 (CS), API 603 (SS)
- INVESTMENT CAST TO 8" (SS ONLY)
- FLEX WEDGE DESIGN FOR POSITIVE SHUTOFF



Figure 461 / 462 - SS
Figure 561 / 562 - CS
FLANGED GLOBE VALVE

- 150# FLANGES (461/561)
- 300# FLANGES (462/562)
- API 600 (CS), API 603 (SS)
- INVESTMENT CAST TO 8" (SS ONLY)
- MODIFIED PLUG TYPE DISC FOR HAND OPERATED THROTTLING



Figure 471 / 472 - SS
Figure 571 / 572 - CS
FLANGED SWING CHECK VALVE

- 150# FLANGES (471/571)
- 300# FLANGES (472/572)
- API 600 (CS), API 603 (SS)
- MACHINED DISC & SEAT FOR TIGHT SHUTOFF



Figure 30F / 30T / 35S
BRAIDED METAL ANNULAR FLEXIBLE CONNECTORS

- STAINLESS STEEL HOSE IN FLANGED (30F) OR MALE THREADED ENDS (30T)
- BRONZE HOSE IN COPPER SWEAT ENDS (35S)
- MAXIMUM OFFSET OF 3/8"



Figure 40
SINGLE SPHERE FLEXIBLE CONNECTOR

- 150# CARBON STEEL FLOATING FLANGES
- WIRE AND FABRIC REINFORCEMENT MOLDED INTO ELASTOMER SPHERE
- SIZES 2-1/2" - 10"



Actuation & Accessories
MANUAL GEAR OPERATORS

- WORM GEARS FOR QUARTER-TURN
- BEVEL GEARS FOR LINEAR MOVEMENT
- VARIOUS SIZES
- AVAILABLE WITH ISO 5211 MOUNTING FOR DIRECT MOUNT VALVES
- MACHINED MOUNTING ADAPTION ALSO AVAILABLE



Actuation & Accessories
PNEUMATIC ACTUATORS

- CYLINDER (PNEUMATIC & HYDRAULIC)
- RACK & PINION
- SCOTCH YOKE
- DOUBLE-ACTING
- SPRING-RETURN



Actuation & Accessories
ELECTRIC VALVE ACTUATORS

- QUARTER-TURN DESIGN
- VARIOUS NEMA CLASSES
- MULTIPLE VOLTAGES AVAILABLE
- DOUBLE-ACTING (STAY IN LAST POSITION) & SPRING-RETURN DESIGNS
- MULTI-TURN & LARGE BODY ELECTRIC ACTUATORS AVAILABEL ON REQUEST



Actuation & Accessories
SOLENOID PILOT VALVES

- DIRECT (NAMUR) MOUNT OR PIPED CONNECTIONS
- VARIOUS NEMA CLASSES
- MULTIPLE VOLTAGES AVAILABLE
- 3-WAY & 4-WAY CONFIGURATION (OTHERS ON REQUEST)
- MANUAL PILOT VALVES IN VARIOUS CONFIGURATIONS ON REQUEST



Actuation & Accessories
VALVE POSITIONERS

- 3-15 PSI SIGNAL (PNEUMATIC)
- 4-20mA SIGNAL (ELECTRO-PNEUMATIC)
- VARIOUS CONFIGURATIONS AND ENCLOSURE RATINGS AVAILABLE
- DIGITAL, SMART, HART® & OTHERS ON REQUEST



Actuation & Accessories
POSITION / LIMIT SWITCHES

- VARIOUS CONFIGURATIONS AND ENCLOSURE RATINGS AVAILABLE
- QUARTER-TURN SELF CONTAINED
- MECHANICAL
- PROXIMITY



Gauges
LIQUID FILLED & MECHANICAL CONTRACTOR'S PRESSURE GAUGES

- 2-1/2" LIQUID FILLED (GLYCERIN)
- 4-1/2" MECHANICAL CONTRACTOR'S
- PRESSURE RANGES FROM 0-30 PSI TO 0-300 PSI



Gauges
ADJUSTABLE ANGLE THERMOMETERS

- LIQUID THERMOMETER (KERSENE)
 - RANGES 0-120, 0-160 OR 30-240 °F
 - ADJUSTABLE IN 10 DEG INCREMENTS
 - BLUE KERSENE FILLED
- DIGITAL SOLAR THERMOMETER
 - -58 TO 100 °F RANGE
 - FIELD SELECTABLE °F OR °C DISPLAY



Gauges
BRASS GAUGE ACCESSORIES

- NEEDLE VALVES
- PRESSURE SNUBBER/FILTERS
- P/T TEST PLUGS
- THERMOWELLS



Piping Products
BOLT INSULATORS

- REINFORCED NYLON 66 RESIN
- WHITE
- SOLD INDIVIDUALLY
- SIZES 1/2", 5/8", AND 3/4"



Piping Products
NUT / BOLT / GASKET KITS

- NON-ASBESTOS KITS
 - RING GASKETS
 - 150# & 300#
 - SIZES 1/2" - 20"
- RED RUBBER KITS
 - RING AND FULL FACE GASKETS
 - 150#
 - SIZES 1/2" - 20"



Piping Products
LUGGED BFV BOLT PACKS

- CARBON STEEL ASTM A307 GRADE A
- ZINC PLATED
- SIZING PER ANSI B18.2.1
- FOR 150# FLANGES
- BOLTS FOR TWO FLANGES PER KIT
- SIZES 2" - 12"



Piping Products
PIPE HANGERS & SUPPORTS

- MALLEABLE IRON
 - PIPE HANGERS
 - BEAM CLAMPS
 - MOUNTING BRACKETS
- PLAIN, ZINC & COPPER FINISH



Piping Products
STRUT ACCESSORIES

- STRUT, TUBE & CONDUIT CLAMPS
- ANGLE FITTING
- CHANNEL NUTS
- POST BASES
- VARIOUS FINISHES

DOC: FNWProduct08 rev. 9/08

© 2008 - FNW. All rights reserved.
 The FNW logo is a registered trademark of Ferguson Enterprises, Inc.

The contents of this publication are presented for information purposes only, and while effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, expressed or implied, regarding the products or services described herein or their use or applicability. All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the designs or specifications of our products at any time without notice. Always verify that you have the most recent product specifications or other documentation prior to the installation of these products.